



REMIS AMERICA

NORTH AMERICA PRODUCT CATALOG



877.997.3647



WWW.REMISAMERICA.COM



REMIS-SAFE FLEX





REMIS-SAFE FLEX

- Energy free door
- Double pane w/ low E coating
- Insulated, non-heated glass pack
- 60° Hold-open & soft close

WARRANTY

- Glass seals: 20 YEAR warranty
- LED lighting: 5 YEAR warranty

FRAME OPTIONS

Black

Gray

DOE COMPLIANT



Premium Black



Premium Gray

HANDLE OPTIONS

ENERGY FREE DOOR



GLASS SPACERS



LED 300K - 400K



HIGH VISIBILITY



QUICK FACTS



LINEUP # OF DOORS	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15
AMPS	0.14	0.24	0.38	0.47	0.61	0.71	0.85	0.94	1.08	1.18	1.32	1.34	1.55	1.65	1.79
WATTS	17	28.3	45.2	56.5	73.4	84.7	101.6	112.9	129.8	141.1	158	160.8	186.2	197.5	214.4
LINEUP # OF DOORS	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
AMPS	1.88	2.02	2.12	2.26	2.35	2.50	2.59	2.73	2.82	2.96	3.06	3.20	3.30	3.43	3.53
WATTS	225.7	242.6	253.9	270.8	282.1	299	310.3	327.2	338.5	355.4	366.7	383.6	394.9	411.8	423.1

INSTALLATION NOTES:

Remisafe Flex hinged doors can be installed in new and remodeled walk-in coolers. No anti-sweat is required with our design. For new coolers, shelving must be placed after doors have been installed and adjusted. For remodels, shelving must be relocated until after doors are installed and adjusted. Most installations are complete in 1 day (by trained technicians) and can be done overnight to minimize disruption at your store. For proper and efficient installation, the walk-in cooler opening MUST be level, plumb, and structurally self-supporting. Remis America will do all required LV electrical wiring (LEDs). A licensed electrician must make the final connection to HV. Remis America warranties our product for 12 months from the date of shipment. This warranty is limited to repair or replacement, at Remis America's discretion. See warranty agreement for complete details.



877.997.3647



WWW.REMISAMERICA.COM

GLASS DOOR: **MULTIDECK**



REMIS-SAFE T MAX



877.997.3647



WWW.REMISAMERICA.COM



REMIS-SAFE T MAX

- Energy free door
- Double pane w/ low E coating
- Insulated, non-heated glass pack
- 60° Hold-open & soft close

WARRANTY

- Glass seals: 20 YEAR warranty
- LED lighting: 5 YEAR warranty



FRAME OPTIONS

Black

Gray

DOE COMPLIANT



HANDLE OPTIONS

ENERGY FREE DOOR

LED 300K - 400K

ELIGIBLE REBATE



QUICK FACTS



LINEUP FOOTAGE	4	6	8	10	12	16	20	24	28	32	36	40	44	48	52	56
AMPS	0.22	0.65	0.44	0.65	0.65	0.87	1.09	1.3	1.52	1.74	1.95	2.17	2.39	2.6	2.82	3.04
WATTS	26	78	52	78	78	104	130	156	182	208	234	260	286	312	338	364
LINEUP FOOTAGE	60	64	68	72	76	80	84	88	92	96	100	104	108	112	116	120
AMPS	3.25	3.47	3.69	3.9	4.12	4.34	4.55	4.77	4.99	5.2	5.42	5.64	5.85	6.07	6.29	6.5
WATTS	390	416	442	468	494	520	546	572	598	624	650	676	702	728	754	780

INSTALLATION NOTES:

Remis Safe T Max hinged doors can be retrofit onto most multi deck case styles. No anti sweat is required with our design. Remis America will send our technical team to take detailed measurements at the store to ensure proper fit of the doors and frames. The OEM canopy lighting will be removed and discarded. We will replace it with new lights on our frame. The OEM canopy hood and lower front cladding will remain in place whenever possible. No product has to be removed from the case prior to or during the door installation. Most installations are complete in 3 or 4 days and can be done overnight to minimize disruption at your store. Remis America will do all required electrical wiring. After doors are installed, the expansion valve superheat and the EPR at the rack need to be reset by a qualified technician. 20 year warranty against seal failure. Remis America warrants our product for 15 months from the date of shipment. This warranty is limited to repair or replacement, at Remis America's discretion. See warranty agreement for complete details.



877.997.3647



WWW.REMISAMERICA.COM



GLASS DOOR: MULTIDECK & COOLER



REMIS-SAFE HG



877.997.3647



WWW.REMISAMERICA.COM

REMIS-SAFE HG





- Energy free door
- Double pane w/ low E coating
- Insulated, non-heated glass pack
- 60° Hold-open & gravity close

WARRANTY

- Glass seals: 20 YEAR warranty
- LED lighting: 5 YEAR warranty



DOE COMPLIANT



HANDLE OPTIONS

FRAME OPTIONS

Black

Gray

ENERGY FREE DOOR



LED 300K - 400K



ELIGIBLE REBATE



QUICK FACTS



	NT	1	2	3	4	5	6	7	8	9	10	11	12
AMPS		0.14	0.24	0.38	0.47	0.61	0.71	0.85	0.94	1.08	1.18	1.32	1.41
WATTS		17	28.3	45.2	56.5	73.4	84.7	101.6	112.9	129.8	141.1	158	169.3
	NT	13	14	15	16	17	18	19	20	21	22	23	24
AMPS		1.55	1.65	1.79	1.88	2.02	2.12	2.26	2.35	2.49	2.59	2.73	2.82
WATTS		186.2	197.5	214.4	225.7	242.6	253.9	270.8	282.1	299	310.3	327.2	338.5

INSTALLATION NOTES:

Remisafe HG hinged doors can be installed into new or existing cooler boxes. No anti sweat is required with our design. Customer must confirm rough opening dimensions to ensure proper fit of the doors and frames. No product has to be removed from the cooler box prior to or during the door installation. Most installations are complete in 1 or 2 days and can be done overnight to minimize disruption at your store. Remis America will do all required low voltage electrical wiring. 20 year warranty against glass seal failure. Remis America warranties our product for 15 months from the date of shipment. This warranty is limited to repair or replacement, at Remis America's discretion. See warranty agreement for complete details.



877.997.3647



WWW.REMISAMERICA.COM

CATALOG



Technical Data	Safe Flex	Safe T MAX	Safe HG
Profiles / Colors	Door profiles top/ bottom in Dark Gray (RAL 7016)	Frame and door profiles in Gray (RAL 7004) Black (RAL 9005)	Frame and door profiles in Gray (RAL 7004) Black (RAL 9005)
Handles	Premium - Stainless Steel Look	Plastic handle gray or black Premium - Black or Premium - Stainless Steel Look	Premium - Black or Premium - Stainless Steel Look
Opening Height*	Standard: 79"	35-1/2 - 78-3/4 in	79"
Opening Width*	Standard: 2' 6-7/16" - 75' 9-13/16"	Standard: 48", 24"	Standard: 60", 30"
Lighting	LED	LED	LED
Required cooler condition	Plumb/level, self-supporting without damage	Plumb and level, without damage	Plumb and level, without damage
Standard insulating glass (IG)	Tempered double pane with 1x low-e coating	Tempered double pane with 1x low-e coating	Tempered double pane with 1x low-e coating
Glass structure	7/8" IG 5/32" single-pane tempered 9/16" argon gas 5/32" single-pane tempered	7/8" IG 1/8" single-pane tempered 5/8" argon gas 1/8" single-pane tempered	7/8" IG 1/8" single-pane tempered 5/8" argon gas 1/8" single-pane tempered
Heat transfer Ug value	0.35 BTU/hr-ft ² -°F	0.35 BTU/hr-ft ² -°F	0.35 BTU/hr-ft ² -°F
Condensation forms at 60% r.h. and a room temperature of:	+87°F**	+87°F**	+87°F**
Dew point	+72°F**	+72°F**	+72°F**
Total reflection	13%	15%	15%
Transparency	80%	79%	79%
Climate class	3M1 (75°F / 55% r.h.)	3M1 (75°F / 55% r.h.)	3M1 (75°F / 55% r.h.)
Closing system	Less than 80° self-close	Cam Closer	Torsion rod self-closure
Energy Consumption	0 kWh (LEDs excluded)	0 kWh (LEDs excluded)	0 kWh (LEDs excluded)

* Custom sizes available

** Vary by store layout and use.

*** Cooler internal tempertaure at 35°F as per DOE